

Control No.GB-ESP-02Date FirstJanuary 16, 2018Date RevisedJanuary 22, 2024

MSDS Number : AA2158-0000000010

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- A. PRODUCT NAME : ESP Series Battery
- B. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

: Electric Storage Battery.

- C. MANUFACTURER/SUPPLIER/DISTRIBUTOR INFORMATION
 - MANUFACTURER : Sebang Global Battery CO.,Ltd.

122, Jeongdong-ro, Changwon-si, Gyeongsangnam-do

TEL: +82-55-279-9734 FAX: +82-55-282-2658

2. HAZARDS IDENTIFICATION

A. HAZARD CLASSIFICATION

PHYSICAL HAZARDS

: Not Classified.

HEALTH HAZARDS

:	Acute toxicity	Category 4 (inhalation)
:	Skin corrosion/irritation	Category 1
:	Serious eye damage/eye irritation	Category 1
:	Carcinogenicity	Category 1B
:	Germ cell mutagenicity	Category 2
:	Specific target organ toxicity - single exposure	Category 1
:	Specific target organ toxicity - repeated exposur	eCategory 1

ENVIRONMENTAL HAZARDS

: Not Classified.

B. GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAMS



SIGNAL WORD : DANGER.

HAZARD STATEMENTS

- H332 Harmful if inhaled.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H350 May cause cancer (inhalation).
- H341 Suspected of causing genetic defects.
- H370 Specific target organ toxicity single exposure; Respiratory tract irritation



C.

Control No.GB-ESP-02Date FirstJanuary 16, 2018Date RevisedJanuary 22, 2024

MSDS Number : AA2158-000000010

H372	Causes damage to organs (Hematopoietic system, kidney, central nervous system, peripheral nervous system, cardiovascular system, immune system, respiratory).
H362	May cause harm to breast-fed children
PRECAUTIONARY ST	ATEMENTS :
[Prevention]	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a wellventilated area.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P281	Use personal protective equipment as required.
P270	Do not eat, drink or smoke when using this product.
[Response]	
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing Rinse skin with water/shower.
P363	Wash contaminated clothing before reuse.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment (see on this label).
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.
P314	Get medical advice/attention if you feel unwell.
[Storage]	
P405	Store locked up.
[Disposal]	
P501	Dispose of contents/container in accordance with local/regional/national regulations.
OTHER HAZARDS WH	IICH DO NOT RESULT IN CLASSIFICATION (e.g. Dust explosion hazards)
NFPA/HMIS Rating	
	Health=3, Flammability=0, Instability=1

(0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme)



Control No.GB-ESP-02Date FirstJanuary 16, 2018Date RevisedJanuary 22, 2024

MSDS Number : AA2158-000000010

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name / Synonym	CAS No.	Content (%)
Lead	7439-92-1	69
Electrolyte (sulfuric acid / water / solution)	7664-93-9	19 - 22
Polypropylene / PP Resin	9003-07-0	7 - 10
Separator	Not available	3 - 4

* European Inventory of Existing Commercial Chemical Substances (EINECS).

4. FIRST AID MEASURES

A. EYE CONTACT	:	If a battery ruptures, do not rub or scratch exposed eye. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. GET MEDICAL ATTENTION IMMEDIATELY.
B. SKIN CONTACT	:	If a battery ruptures, do not rub or scratch exposed skin. If liquid get on the skin, immediately flush the contaminated skin with water for at least 15 minutes. If liquid penetrate through the clothing, immediately remove the clothing and shoes under a safety shower and continue to wash the skin for at least 15 minutes. GET MEDICAL ATTENTION IMMEDIATELY.
C. INHALATION	:	If a battery ruptures, move to fresh air in case of accidental inhalation of mist. If breathing has stopped, perform artificial respiration. If breathing is difficult, give oxygen. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.
D. INGESTION	:	If solutions of a battery chemicals have been swallowed and the person is conscious, give one glass of water. Vomiting may occur spontaneously, but Do NOT induce vomiting. Never give anything by mouth to an unconscious person. GET MEDICAL ATTENTION IMMEDIATELY.
E. MOST IMPORTANT	SYN	MPTOMS/EFFECTS, ACUTE OR DELAYED
EYES	:	Not a likely route of exposure. If a battery ruptures, direct contact with the liquid or exposure to vapors or mists may cause tearing, redness, swelling, corneal damage and irreversible eye damage. Splashes in the eyes will cause severe burns.
SKIN	:	Not a likely route of exposure. Direct contact with internal components of a battery can be severely irritating to the skin and may result in redness, swelling, burns and severe skin damage. Skin contact may aggravate an existing dermatitis condition.
INHALATION	:	Not a likely route of exposure. If a battery ruptures, may be harmful or fatal if inhaled in a confined area. May cause severe irritation and burns of the nose, throat and respiratory tract.
INGESTION	:	Not a likely route of exposure. Causes serious burns of the mouth or perforation of the esophagus or stomach. May be fatal if swallowed.

* Lead may causes toxic to blood, kidneys, central nervous system (CNS). Repeated or prolonged exposure to lead can produce target organs damage.

F. INDICATION OF IMMEDIATE MEDICAL ATTENTION AND NOTES FOR PHYSICIAN



Control No.	GB-ESP-02
Date First	January 16, 2018
Date Revised	January 22, 2024

MSDS Number : AA2158-000000010

Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition.

5. FIRE FIGHTING MEASURES

- A. SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA
 - Use extinguishing media appropriate for surrounding fire.
 - If a battery ruptures, use dry chemical, soda ash, lime, sand or carbon dioxide.
- B. SPECIFIC HAZARDS ARISING FROM THE CHEMICAL
 - Lead, lead compounds and sulfuric acid fume may be released during a fire involving the product.
- C. SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS
 - Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing.
- D. FIRE AND EXPLOSION HAZARD

Not flammable.

: Battery may rupture due to pressure buildup when exposed to excessive heat and may be result in the release of corrosive materials.

6. ACCIDENTAL RELEASE MEASURES

A. NECESSARY MEASURES AND PROTECTIVE GEAR TO PROTECT HUMANS

- If a battery ruptures, avoid contact with skin, eyes and clothing. Do not touch spilled material. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection).
- B. NECESSARY MEASURES TO PROTECT ENVIRONMENT

2

- Notify authorities and appropriate federal, state, and local agencies. Prevent the product from spreading into the environment. Avoid direct discharge into drains.
- C. METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP
 - SMALL SPILLS: Collect all released material in a plastic lined metal container. If necessary neutralize the residue with a dilute solution of sodium carbonate. Wash affected area.
 - LARGE SPILLS: Contain liquid using absorbent material, by digging trenches or
 - by building a dike. Absorb with dry earth, sand or other non-combustible material. Neutralize the residue with a dilute solution of sodium carbonate. Dispose of all contaminated materials in accordance with current local regulations.

7. HANDLING AND STORAGE

A. PRECAUTIONS FOR SAFE HANDLING

Protect from physical damage.

		Control No.	GB-ESP-02
SEBANG	Material Safety Data sheet (MSDS)	Date First	January 16, 2018
BANG		Date Revised	January 22, 2024

MSDS Number : AA2158-000000010

B. CONDITIONS FOR SAFE STORAGE (INCLUDING ANY INCOMPATIBILITIES)

Avoid contact with eyes. Store in a cool, dry, ventilated area away from sources
of heat, moisture, incompatibilities, and direct sunlight. Have emergency equipment (for fires, spills, leaks, etc.) readily available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. OCCUPATIONAL EXPOSURE LIMIT(S), BIOLOGICAL EXPOSURE STANDARD

OSHA-PEL 0.05 mg/m3 (Lead), 1 mg/m3 (Sulfuric acid)

ACGIH-TLV TWA 0.05 mg/m3 (Lead), TWA 0.2 mg/m3 (Sulfuric acid)

- B. APPROPRIATE ENGINEERING CONTROLS
 - : Use local exhaust ventilation if necessary to control airborne mist and vapor.
- C. INDIVIDUAL PROTECTION MEASURES

Respiratory protection :	If significant mists or aerosols are generated an approved respirator is recommended. If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection.
Eye protection :	Wear safety glasses with side shields (or goggles).
Hand protection :	Wear chemical resistant gloves. Gloves should be replaced immediately if signs of degradation are observed.
Body protection :	Use good work and personal hygiene practices to avoid exposure. Consider the provision in the work area of a safety shower and eyewash. Always wash thoroughly after handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

A. APPEARANCE (PHY	SIC	AL STATE, COLOUR etc.)	:	Off-white cloudy liquid with solid object.
B. Odour	:	Characteristics.		
C. ODOR THRESHOLD	:	Not available.		
D. pH	:	pH < 1 (Sulfuric acid)		
E. MELTING POINT/FR	EEZ	ZING POINT	:	Not available.
F. INITIAL BOILING PO	INT	AND BOILING RANGE	:	Not available.
G. FLASH POINT	:	Non-flammable.		
H. EVAPORATION RAT	Е		:	Not available.
I. FLAMMABILITY (SOL	_ID,	GAS)	:	Not applicable.
J. UPPER/LOWER FLA	ΜN	IABILITY OR EXPLOSIVE L	IMITS	
	:	Non-flammable.		
K. VAPOR PRESSURE	:	Not available.		
L. SOLUBILITY	:	Soluble in water.		

M. VAPOR DENSITY : Not available.

				Control No.	GB-ESP-02
SEBANG Mat	erial Safety Data	a sh	eet (MSDS)	Date First	January 16, 2018
				Date Revised	January 22, 2024
			MSDS Number	: AA2158-00	00000010
N. SPECIFIC GRAVITY : Not	available.				
O. PARTITION COEFFICIENT C		:	Not available.		
P. AUTO-IGNITION TEMPERAT	URE	:	Not applicable.		
Q. DECOMPOSITION TEMPERA	ATURE	:	Not available.		
R. VISCOSITY : Not	available.				
S. MOLECULAR WEIGHT		:	Mixture.		
Note: These physical properties a	are typical values for th	nis pro	oduct.		
A. APPEARANCE (PHYSICAL S	TATE, COLOUR etc.)	:	Bluish white, silver	ry gray.	
B. Odour : Non	ie.				
C. ODOR THRESHOLD : Not	available.				
D. pH : Not	applicable.				
E. MELTING POINT/FREEZING	POINT	:	327.5℃		
F. INITIAL BOILING POINT AND	D BOILING RANGE	:	1740℃ (1013 hPa)	
G. FLASH POINT : Non	-flammable.				
H. EVAPORATION RATE		:	Not applicable.		
I. FLAMMABILITY (SOLID, GAS	5)	:	Not applicable.		
J. UPPER/LOWER FLAMMABIL	ITY OR EXPLOSIVE LI	MITS			
: Non	-flammable.				
K. VAPOR PRESSURE : 1.33	3 hPa (973℃)				
L. SOLUBILITY : Insc	oluble in water.				
M. VAPOR DENSITY : Not	applicable.				
N. SPECIFIC GRAVITY : 11.3	34 g/cm3				
O. PARTITION COEFFICIENT C	F n-OCTANOL/WATE	:	Not applicable.		
P. AUTO-IGNITION TEMPERAT	URE	:	Not applicable.		
Q. DECOMPOSITION TEMPERA	ATURE	:	Not applicable.		
R. VISCOSITY : Not	applicable.				
S. MOLECULAR WEIGHT		:	207.2		

Note: These physical properties are typical values for Lead(Pb).

10. STABILITY AND REACTIVITY

A. CHEMICAL STABILIT: Stable at normal temperatures and storage conditions.

B. POSSIBILITY OF HAZARDOUS REACTIONS

1

- : Hazardous polymerization will not occur.
- C. CONDITIONS TO AVOID (STATIC DISCHARGE, SHOCK, VIBRATION etc.):
 - Overcharging. Sources of ignition. Mechanical impact. Contact with incompatible chemicals.
- D. SUBSTANCES TO AVOID
 - : If a battery ruptures, avoid contact with organic materials and alkaline materials.

		Control No.	GB-ESP-02
SEBANG	Material Safety Data sheet (MSDS)	Date First	January 16, 2018
BANG		Date Revised	January 22, 2024

MSDS Number : AA2158-000000010

E. HAZARDOUS DECOMPOSITION PRODUCTS

Lead, Lead compounds and sulfuric acid fumes may be released during a fire involving the product.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure						
Inhalation :	•	Corrosive. severe irritation and burns.				
Ingestion :	Serious burns.					
Eye/Skin						
Eye :	Tearing, redness, swelling, corneal damage, irreversible eye damage a severe burns.					
Skin :	Redness, swelling, burns a	and se	evere skin damage.			
B. Delayed and immediate	effects and also chronic effe	ffects and also chronic effects from short and long term exposure				
Acute toxicity (possible r	oute of exposure)	:				
Oral (LD50) :	Rat	214	0 mg/kg (Sulfuric acid)			
Skin (LD50):	Not available.					
Inhalation (LC50) :	Rat	0.09	94 mg/L(4hr) (dust//mist)			
Skin corrosion/irritation		:	cat 1			
Serious eye damage/irrit	ation	:	cat 1			
Respiratory sensitization		:	Not available.			
Skin sensitization :	Not available.					
Carcinogenicity :	cat 1B					
	* Note: Sulfuric acid mist is	s not e	1 (Mist containing sulfuric acid) expected under normal use of the product. 2B (Lead), IARC Group 3 (ABS Resin)			
Germ cell mutagenicity		:	cat 2			
Reproductive toxicity :	Not available.					
STOST-single exposure		:	cat 1			
:	Respiratory.					
STOST-repeated exposu	ure	:	cat 1			
:		•	central nervous system, peripheral nervous immune system, respiratory.			
Aspiration hazard :	Not available.					
C. Numeric measure of toxicity (such as acute toxicity estimates) - ATEmix						
Oral (LD50) :	Rat	> 5,0	000 mg/kg			
Skin (LD50) :	Not available.					
Inhalation (LC50) :	Rat	2.51	mg/L(4hr) (dust//mist)			
. ,						



Material Safety Data sheet (MSDS)

Control No.	GB-ESP-02		
Date First	January 16, 2018		
Date Revised	January 22, 2024		

MSDS Number : AA2158-000000010

12. ECOLOGICAL INFORMATION

- A. Aquatic/terrestrial ecology toxicity
 - Fish (LC50) : Not available.
 - Daphnia (EC50) : Not available.
 - Algae (EC50) : Not available.
- B. Persistence and degradability
 - Persistence : Not available.
 - Degradability : Not available.
- C. Bioaccumulative potential
- : Not available.
- D. Mobility in soil : Not available.
- E. Other hazardous effects

Not available.

5

13. DISPOSAL CONSIDERATIONS

A. DISPOSAL METHODS

Dispose of in accordance with local, state, and federal regulations. Hazardous wastes must be transported by a licensed hazardous waste transporter and

- disposed of or treated in a properly licensed hazardous waste treatment, storage, disposal or recycling facility. Consult local, state, and federal regulations for specific requirements.
- B. PRECAUTIONS (INCLUDING DISPOSAL OF CONTAMINATED CONTAINER OR PACKAGE)
 - Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. TRANSPORT INFORMATION

All Global's ESP series are valve regulated lead acid (VRLA) batteries. GLOBAL's VRLA batteries meet test specifications for "non-spillable electric storage batteries", as required by D.O.T., 49 CFR 173. 159(d), and IMO/IMDG, and ICAO/IATA packing instruction 872 and note A67; therefore, are non-regulated when protected against short circuits, kept upright, and securely packaged. The battery and the outer packaging must be plainly and durably marked "NONSPILLABLE BATTERY" or "NONSPILLABLE".

These batteries meet the requirements contained in the following special provisions.

- A. Regulatory Body Special provisions
- B. U. S. DOT Unregulated, meets the requirement of 49 CFR 173.159(d)
- C. IATA / ICAO Unregulated, meets the requirements of Special Revisions A67
- D. IMO IMDG Unregulated, meets the requirements of Special Revisions #238
- E. UN Number 2800
- * Proper Shipping Name : Batteries, wet, non-spillable



Control No.GB-ESP-02Date FirstJanuary 16, 2018Date RevisedJanuary 22, 2024

MSDS Number : AA2158-000000010

15. REGULATORY INFORMATION

■ INVENTORIES
EINECS/EU: Listed (EINECS No. 231-100-4(Lead), 231-639-5(Sulfuric acid))
TSCA/US : Listed.
ENCS/JAPAN: Listed (ENCS No. 1-527(Lead), 1-430(Sulfuric acid))
AICS/AUSTRALIA : Listed.
DSL/CANADA : Listed.
IECSC/CHINA : Listed.
PICCS/PHILIPPINES : Listed.
KECI/S.KOREA: Listed (KE-21887(Lead), KE-32570(Sulfuric acid))
■ International Environmental Agreement
PIC : Not listed.
POPs : Not listed.
Ozone depletion : Not listed.
EU. Directive 67/548/EEC on the classification, packaging, and labelling of dangerous substances, Annex I
Classification: C; R35
Risk Phrases: R35
Safety Phrases : S1/2, S26, S30, S45
₪ U.S. Federal, Heanth and Environment) and U.S. Federal, Right-To-Know
CERCLA Section 103 (40 CFR 302.4)
: 10lb (4.535 kg) (Lead), 1000 lb (453.599 kg) (Sulfuric acid)
EPCRA (SARA Title III) Section 302 (EHS -TPQ)
: 1000 lb (453.599 kg) (Sulfuric acid)
EPCRA (SARA Title III) Section 304 (EHS - Reporting Quantities)
: 1000 lb (453.599 kg) (Sulfuric acid)
EPCRA (SARA Title III) Section 313 - Toxic chemical release reporting
Sulfuric acid (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)
OSHA Specifically Regulated Substances (29 CFR 1910.10011052)
: Not applicable.
□ CANADA REGULATORY INFORMATION
WHMIS Ingredient Disclosure List : Regulated.
NOTE: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.
6. OTHER INFORMATION



Date FirstJanuary 16, 2018Date RevisedJanuary 22, 2024

GB-ESP-02

MSDS Number : AA2158-000000010

Control No.

Guideline for Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

EC-ECB, International Uniform Chemical Information Database (IUCLID)

Hazardous Substances Data Bank (HSDB)

Registry of Toxic Effects of Chemical Substances (RTECS)

National Institute of Technology and Evaluatio -NITE (Japan).

NFPA 704 Standard System for the Identification of the Hazards of Materials for Emergency Response.

International Chemical Safety Cards(ICSC)(http://www.nihs.go.jp/ICSC) **3E Company/Ariel WebInsight DB**.

B. THE DATE OF PREPARATION OF THE MSDS : January 16, 2018

C. THE DATE OF PREPARATION OF THE LATEST REVISION

: January 22, 2024

D. OTHER INFORMATIO:

The above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Sebang Global Battery CO.,Ltd. shall not be held liable for any damage resulting from handling or from contact with the above product. Each individual should make a determination as to the suitability of the information for their particular purpose(s). Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.