

Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

A. PRODUCT NAME : VGS Series

B. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

: Electric Storage Battery.

C. MANUFACTURER/SUPPLIER/DISTRIBUTOR INFORMATION

MANUFACTURER : Sebang Global Battery CO.,Ltd.

122, Jeongdong-ro, Changwon-si, Gyeongsangnam-do

TEL: +82-55-279-9734 FAX: +82-55-282-2658

### 2. HAZARDS IDENTIFICATION

### A. HAZARD CLASSIFICATION

PHYSICAL HAZARDS

Not Classified.

**HEALTH HAZARDS** 

: Acute toxicity Category 4 (inhalation)

Skin corrosion/irritation
 Serious eye damage/eye irritation
 Category 1
 Carcinogenicity
 Germ cell mutagenicity
 Specific target organ toxicity – single exposure
 Category 2
 Specific target organ toxicity – repeated exposure Category 1

## **ENVIRONMENTAL HAZARDS**

Not Classified.

### B. GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAMS



SIGNAL WORD : DANGER.

HAZARD STATEMENTS

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.H350 May cause cancer (inhalation).

H341 Suspected of causing genetic defects.

H370 Specific target organ toxicity – single exposure; Respiratory tract irritation



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

Causes damage to organs (Hematopoietic system, kidney, central nervous system, peripheral nervous system, cardiovascular system, immune system, respiratory).

H362 May cause harm to breast-fed children

PRECAUTIONARY STATEMENTS	
I NECACTIONALLI STATEMENTS	

## [Prevention]

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a wellventilated area.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P281 Use personal protective equipment as required.

P270 Do not eat, drink or smoke when using this product.

## [Response]

P304 + P340

IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P363 Wash contaminated clothing before reuse.

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see ... on this label).

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P307+P311 IF exposed: Call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

[Storage]

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national regulations.

C. OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION (e.g. Dust explosion hazards) NFPA/HMIS Rating

Health=3, Flammability=0, Instability=1 (0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme)



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name / Synonym	CAS No. or ID	Content (%)
Lead	7439-92-1 / 231-100-4*	64
Electrolyte (sulfuric acid / water / solution)	7664-93-9 / 231-639-5*	13 - 17
Phosphoric acid	7664-38-2 / 231-633-2*	3 - 4
Butadiene-Acrylonitrile-Styrene copolymer / ABS Resin	9003-56-9 / exempted	7 - 10
Silica, amorphous, fumed, crystfree	112945-52-5 / included	7 - 10
Separator	Not available	7 - 10

<sup>\*</sup> European Inventory of Existing Commercial Chemical Substances (EINECS).

#### 4. FIRST AID MEASURES

If a battery ruptures, do not rub or scratch exposed eye. Immediately flush eyes

A. EYE CONTACT : with running water for at least 15 minutes, keeping eyelids open. Cold water

may be used. GET MEDICAL ATTENTION IMMEDIATELY.

If a battery ruptures, do not rub or scratch exposed skin. If liquid get on the skin,

immediately flush the contaminated skin with water for at least 15 minutes. If liquid penetrate through the clothing, immediately remove the clothing and

B. SKIN CONTACT : liquid penetrate through the clothing, immediately remove the clothing and

shoes under a safety shower and continue to wash the skin for at least 15

minutes. GET MEDICAL ATTENTION IMMEDIATELY.

If a battery ruptures, move to fresh air in case of accidental inhalation of mist. If

C. INHALATION : breathing has stopped, perform artificial respiration. If breathing is difficult, give

oxygen. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

If solutions of a battery chemicals have been swallowed and the person is

D. INGESTION conscious, give one glass of water. Vomiting may occur spontaneously, but Do

NOT induce vomiting. Never give anything by mouth to an unconscious person.

GET MEDICAL ATTENTION IMMEDIATELY.

E. MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE OR DELAYED

Not a likely route of exposure. If a battery ruptures, direct contact with the liquid

or exposure to vapors or mists may cause tearing, redness, swelling, corneal

damage and irreversible eye damage. Splashes in the eyes will cause severe

burns.

Not a likely route of exposure. Direct contact with internal components of a

SKIN battery can be severely irritating to the skin and may result in redness, swelling,

burns and severe skin damage. Skin contact may aggravate an existing

dermatitis condition.

Not a likely route of exposure. If a battery ruptures, may be harmful or fatal if

INHALATION : inhaled in a confined area. May cause severe irritation and burns of the nose,

throat and respiratory tract.

Not a likely route of exposure. Causes serious burns of the mouth or perforation

of the esophagus or stomach. May be fatal if swallowed.



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

# F. INDICATION OF IMMEDIATE MEDICAL ATTENTION AND NOTES FOR PHYSICIAN

Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition.

#### 5. FIRE FIGHTING MEASURES

#### A. SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA

- Use extinguishing media appropriate for surrounding fire.
- If a battery ruptures, use dry chemical, soda ash, lime, sand or carbon dioxide.
- B. SPECIFIC HAZARDS ARISING FROM THE CHEMICAL
  - Lead, lead compounds and sulfuric acid fume may be released during a fire involving the product.
- C. SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS
  - Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing.
- D. FIRE AND EXPLOSION HAZARD
  - Not flammable.
  - Battery may rupture due to pressure buildup when exposed to excessive heat and may be result in the release of corrosive materials.

### 6. ACCIDENTAL RELEASE MEASURES

### A. NECESSARY MEASURES AND PROTECTIVE GEAR TO PROTECT HUMANS

If a battery ruptures, avoid contact with skin, eyes and clothing. Do not touch spilled material. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection).

### B. NECESSARY MEASURES TO PROTECT ENVIRONMENT

Notify authorities and appropriate federal, state, and local agencies. Prevent the product from spreading into the environment. Avoid direct discharge into drains.

# C. METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

SMALL SPILLS: Collect all released material in a plastic lined metal container. If necessary neutralize the residue with a dilute solution of sodium carbonate. Wash affected area.

LARGE SPILLS: Contain liquid using absorbent material, by digging trenches or by building a dike. Absorb with dry earth, sand or other non-combustible material. Neutralize the residue with a dilute solution of sodium carbonate. Dispose of all contaminated materials in accordance with current local regulations.

#### 7. HANDLING AND STORAGE

<sup>\*</sup> Lead may causes toxic to blood, kidneys, central nervous system (CNS). Repeated or prolonged exposure to lead can produce target organs damage.



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

A. PRECAUTIONS FOR SAFE HANDLING

Protect from physical damage.

B. CONDITIONS FOR SAFE STORAGE (INCLUDING ANY INCOMPATIBILITIES)

Avoid contact with eyes. Store in a cool, dry, ventilated area away from sources

of heat, moisture, incompatibilities, and direct sunlight. Have emergency

equipment (for fires, spills, leaks, etc.) readily available.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. OCCUPATIONAL EXPOSURE LIMIT(S), BIOLOGICAL EXPOSURE STANDARD

0.05 mg/m3 (Lead), 1 mg/m3 (Sulfuric acid), 1 mg/m3 (Phosphoric acid), 0.1 OSHA-PEL

mg/m3 (Silica (amorphous silica, fused) (respirable dust))

TWA 0.05 mg/m3 (Lead), TWA 0.2 mg/m3 (Sulfuric acid), TWA 1 mg/m3, STEL

3 mg/m3 (Phosphoric acid), TWA 0.1 mg/m3 (Silica (amorphous silica, fused) **ACGIH-TLV** 

(respirable dust))

B. APPROPRIATE ENGINEERING CONTROLS

Use local exhaust ventilation if necessary to control airborne mist and vapor.

C. INDIVIDUAL PROTECTION MEASURES

If significant mists or aerosols are generated an approved respirator is

recommended. If respiratory protection is required, institute a complete Respiratory protection:

respiratory protection program including selection, fit testing, training,

maintenance and inspection.

Wear safety glasses with side shields (or goggles). Eye protection

Wear chemical resistant gloves. Gloves should be replaced immediately if signs Hand protection

of degradation are observed.

Use good work and personal hygiene practices to avoid exposure. Consider the

provision in the work area of a safety shower and eyewash. Always wash Body protection

thoroughly after handling chemicals.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

A. APPEARANCE (PHYSICAL STATE, COLOUR etc.) : Off-white cloudy liquid with solid object.

B. Odour Characteristics. C. ODOR THRESHOLD: Not available.

D. pH pH < 1 (Sulfuric acid)

Not available. E. MELTING POINT/FREEZING POINT F. INITIAL BOILING POINT AND BOILING RANGE Not available.

G. FLASH POINT : Non-flammable.

H. EVAPORATION RATE Not available.



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

I. FLAMMABILITY (SOLID, GAS) : Not applicable.

J. UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS

Non-flammable.

K. VAPOR PRESSURE : Not available.
L. SOLUBILITY : Soluble in water.
M. VAPOR DENSITY : Not available.
N. SPECIFIC GRAVITY : Not available.

O. PARTITION COEFFICIENT OF n-OCTANOL/WATEI: Not available.
 P. AUTO-IGNITION TEMPERATURE: Not applicable.
 Q. DECOMPOSITION TEMPERATURE: Not available.

R. VISCOSITY : Not available.

S. MOLECULAR WEIGHT : Mixture.

#### 10. STABILITY AND REACTIVITY

A. CHEMICAL STABILIT: Stable at normal temperatures and storage conditions.

B. POSSIBILITY OF HAZARDOUS REACTIONS

Hazardous polymerization will not occur.

C. CONDITIONS TO AVOID (STATIC DISCHARGE, SHOCK, VIBRATION etc.):

Overcharging. Sources of ignition. Mechanical impact. Contact with

incompatible chemicals.

D. SUBSTANCES TO AVOID

: If a battery ruptures, avoid contact with organic materials and alkaline materials.

E. HAZARDOUS DECOMPOSITION PRODUCTS

Lead, Lead compounds and sulfuric acid fumes may be released during a fire

involving the product.

### 11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

Inhalation : Corrosive. severe irritation and burns.

Ingestion : Serious burns.

Eye/Skin

Tearing, redness, swelling, corneal damage, irreversible eye damage and

Eye : severe burns.

Skin : Redness, swelling, burns and severe skin damage.

B. Delayed and immediate effects and also chronic effects from short and long term exposure

Acute toxicity (possible route of exposure)



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

## MSDS Number: AA2158-0000000022

Oral (LD50): Rat 2140 mg/kg (Sulfuric acid),

1530 mg/kg (Phosphoric acid)

Skin (LD50): Rabbit 2740mg/kg (Phosphoric acid)

Inhalation (LC50): Rat 0.094 mg/L(4hr) (dust//mist)

Skin corrosion/irritation : cat 1
Serious eye damage/irritation : cat 1

Respiratory sensitization : Not available.

Skin sensitization : Not available.

Carcinogenicity : cat 1B

ACGIH Group A2, IARC Group 1 (Mist containing sulfuric acid)

\* Note: Sulfuric acid mist is not expected under normal use of the product. ACGIH Group A3, IARC Group 2B (Lead), IARC Group 3 (ABS Resin)

Germ cell mutagenicity : cat 2

Reproductive toxicity: Not available.

STOST-single exposure : cat 1

Respiratory.

STOST-repeated exposure : cat 1

Hematopoietic system, kidney, central nervous system, peripheral nervous

system, cardiovascular system, immune system, respiratory.

Aspiration hazard : Not available.

C. Numeric measure of toxicity (such as acute toxicity estimates) - ATEmix

Oral (LD50) : Rat > 5,000 mg/kg Skin (LD50) : Rabbit > 5,000 mg/kg

Inhalation (LC50): Rat 2.51 mg/L(4hr) (dust//mist)

### 12. ECOLOGICAL INFORMATION

A. Aquatic/terrestrial ecology toxicity

Fish (LC50) : Not available.

Daphnia (EC50) : Not available.

Algae (EC50) : Not available.

B. Persistence and degradability

Persistence : Not available.

Degradability : Not available.

C. Bioaccumulative potential

Not available.

D. Mobility in soil : Not available.

E. Other hazardous effects : Not available.



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

#### 13. DISPOSAL CONSIDERATIONS

#### A. DISPOSAL METHODS

Dispose of in accordance with local, state, and federal regulations. Hazardous wastes must be transported by a licensed hazardous waste transporter and disposed of or treated in a properly licensed hazardous waste treatment, storage, disposal or recycling facility. Consult local, state, and federal regulations for specific requirements.

### B. PRECAUTIONS (INCLUDING DISPOSAL OF CONTAMINATED CONTAINER OR PACKAGE)

Since emptied containers retain product residue, follow label warnings even after container is emptied.

#### 14. TRANSPORT INFORMATION

All Global's VGS series are valve regulated lead acid (VRLA) batteries. GLOBAL's VRLA batteries meet test specifications for "non-spillable electric storage batteries", as required by D.O.T., 49 CFR 173. 159(d), and IMO/IMDG, and ICAO/IATA packing instruction 872 and note A67; therefore, are non-regulated when protected against short circuits, kept upright, and securely packaged. The battery and the outer packaging must be plainly and durably marked "NONSPILLABLE BATTERY" or "NONSPILLABLE".

These batteries meet the requirements contained in the following special provisions.

A. Regulatory Body Special provisions

B. U. S. DOT Unregulated, meets the requirement of 49 CFR 173.159(d)
 C. IATA / ICAO Unregulated, meets the requirements of Special Revisions A67
 D. IMO IMDG Unregulated, meets the requirements of Special Revisions #238

E. UN Number 2800

#### 15. REGULATORY INFORMATION

**□** INVENTORIES

EINECS/EU: Listed (EINECS No. 231-100-4, 231-639-5, 231-633-2)

TSCA/US: Listed.

ENCS/JAPAN: Listed (ENCS No. 1-527, 1-430, 1-422, 6-176)

AICS/AUSTRALIA: Listed.

DSL/CANADA: Listed.

IECSC/CHINA: Listed.

PICCS/PHILIPPINES: Listed.

KECI/S.KOREA: Listed (KE-21887, KE-32570, KE-27427, KE-29398, KE-30953)

■ International Environmental Agreement

PIC : Not listed.
POPs : Not listed.

<sup>\*</sup> Proper Shipping Name: Batteries, wet, non-spillable



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

MSDS Number: AA2158-0000000022

Ozone depletion : Not listed.

EU. Directive 67/548/EEC on the classification, packaging, and labelling of dangerous substances, Annex I

Classification: C; R35 Risk Phrases: R35

Safety Phrases: S1/2, S26, S30, S45

□ U.S. Federal, Heanth and Environment) and U.S. Federal, Right-To-Know

CERCLA Section 103 (40 CFR 302.4)

10lb (4.535 kg) (Lead), 1000 lb (453.599 kg) (Sulfuric acid), 5000 lb

(2267.995 kg) (Phosphoric acid)

EPCRA (SARA Title III) Section 302 (EHS -TPQ)

: 1000 lb (453.599 kg) (Sulfuric acid)

EPCRA (SARA Title III) Section 304 (EHS - Reporting Quantities)

: 1000 lb (453.599 kg) (Sulfuric acid)

EPCRA (SARA Title III) Section 313 - Toxic chemical release reporting

Sulfuric acid (acid aerosols including mists, vapors, gas, fog, and other

airborne forms of any particle size)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-.1052)

: Not applicable.

#### □ CANADA REGULATORY INFORMATION

WHMIS Ingredient Disclosure List: Regulated.

NOTE: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

#### 16. OTHER INFORMATION

### A. SOURCE OF DATA:

Guideline for Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

EC-ECB, International Uniform Chemical Information Database (IUCLID)

Hazardous Substances Data Bank (HSDB)

Registry of Toxic Effects of Chemical Substances (RTECS)

National Institute of Technology and Evaluatio -NITE (Japan).

NFPA 704 Standard System for the Identification of the Hazards of Materials for Emergency Response.

International Chemical Safety Cards(ICSC)(http://www.nihs.go.jp/ICSC)

3E Company/Ariel WebInsight DB.

B. THE DATE OF PREPARATION OF THE MSDS : May 16, 2008

C. THE DATE OF PREPARATION OF THE LATEST REVISION

January 22, 2024

D. OTHER INFORMATIO:



Control No.	GB-VGS-02
Date First	May 16, 2008
Date Revised	January 22, 2024

### MSDS Number : AA2158-0000000022

The above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Sebang Global Battery CO.,Ltd. shall not be held liable for any damage resulting from handling or from contact with the above product. Each individual should make a determination as to the suitability of the information for their particular purpose(s). Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.